



Razor™ Series Towable Magnetic Sweeper

Efficient and cost-effective designed to clear extensive ground areas

Solutions for Commercial Yards & Facility Managers

The Razor Series is designed to clear extensive ground areas. Purpose-built to eliminate down-time expenses caused by flat tires, the Razor easily hooks behind your existing utility vehicles to sweep away dangerous nails, screws, and scrap metal fragments from gravel roads, concrete parking lots, and paved environments.

Proactive Fleet Armor

- Sweeps lots clean to drastically reduce tire repairs and improve site safety
- Built with premium magnets packed end-to-end for uniform, unyielding lifting capability across the entire path

Lightweight Towing Profile

- Engineered specifically for applications where heavy hanging magnets are impractical
- Easily attaches behind ATVs, forklifts, utility vehicles, tractors, or commercial mowers to complete cleanups much faster than alternative methods.

Triple-Setting Height Control:

- Features an integrated three-position wheel adjustment system that allows operators to lock in ground clearances at 1", 2", or 3".

Rust-Proof Architecture

- Constructed from durable, heavy-duty aluminum that resists corrosion and rust, even when left outdoors indefinitely.



14250 Judicial Road, Burnsville, MN 55306

T: 651-272-2950 email: info@msamagnetics.com web: msamagnetics.com



Why let hidden scrap metal dictate your fleet's repair costs and puncture your budget?

Contact MSA Magnetix today! Visit msamagnetics.com

Technical Specifications:

Product Name	Razor - Towable Magnetic Sweeper	
Sweeping Width	Available in 3', 4', 5', 6', 7', 8' lengths	
Height of Sweeper Magnetic Housing	Available in 3" or 4.5"	
Face Depth of Sweeper Magnetic Housing	Available in 3" or 4.5"	
Magnet Dimensions Inside Housing	i.e. Razor50(3"x3") - 48"L x 2"H x 2.5"W; i.e. Razor50(4"x4") - 48"L x 3"H x 4"W	
Steel Plate	Yes	
Ground Clearance	1", 2", or 3" (refer to height adjustability)	
Total Product Weight	Razor38(3"x3")- 48lb Razor50(3"x3")- 60lb Razor62(3"x3")- 73lb Razor74(3"x3")- 85lb Razor86(3"x3")- 98lb	Razor98(3"x3")- 110lb Razor38(4.5"x4.5")- 95lb Razor50(4.5"x4.5")- 120lb Razor62(4.5"x4.5")- 147lb
Lifting Weight (measured in 2.5" 8 penny nails)	Razor38(3"x3")- 30lb Razor50(3"x3")- 40lb Razor62(3"x3")- 50lb Razor74(3"x3")- 60lb Razor86(3"x3")- 70lb	Razor98(3"x3")- 80lb Razor38(4.5"x4.5")- 60lb Razor50(4.5"x4.5")- 80lb Razor62(4.5"x4.5")- 100lb
Cleaning Method	Wipe with glove or rag	
Wheels	Steel 8" ballbearing	
Height Adjustability	Razor(3"x3") - 1", 2" or 3" by moving axle position Razor(4.5"x4.5") - 1", 2" or 3" by moving axle position	
Tongue Weight	N/A	
Frame Construction	Aluminum	
Housing Construction	1/8" Aluminum	
Magnetic Surface Area (square inches)	Razor38(3"x3")- 90" Razor50(3"x3")-120" Razor62(3"x3")-150"	Razor74(3"x3")-180" Razor86(3"x3")-210" Razor98(3"x3")-240"
Maximum Lifting Height (measured in 2 1/2" 8 penny nails)	Razor(3"x3") - 6" Razor(4.5"x4.5") - 8.5"	
Maintenance Requirements	None	
Maximum Operation Speed	Razor(3"x3") - 5 mph/8kph at 3" height Razor(4.5"x4.5") - 8 mph/12kph at 3" height	